



Plug and Play

Plug and Play is the easiest and most simple way to upload content to the screen. Copy paste files conveniently from USB stick to Pyrotech ultra slim digital kiosk and play seamlessly

Network CMS Upgrade

We, at Pyrotech, also offer cloud based Network CMS, if required, and you can run the third party Digital Signage software via our Android PC board too.

Commercial Grade

Designed for use in commercial applications, this screen can run 24/7. Tampering is avoided, as there are no external buttons nor controls.

LED Backlight

Improves brightness and contrast as well as improving their life-span and reducing their power consumption. Unlike other forms of light, this technology is mercury free, making it even more eco-friendly. The panel and back light have a life-span in excess of 60,000 hours.

Giant Tablet Styling

Designed as one giant tablet, the ultra-slim and elegant look is achieved with a rugged and striking aluminum casing and a stunning IPX 1 rated edge-to-edge glass.

IPS Panel

Superior image quality and color depth at 178° ultra wide viewing angle in both, landscape and portrait orientations.



Plug and Play

*On Demand



24/7 Usage

**On Demand



Scheduling Software*



Android Media Player**



IPS Panel Technology



LED Backlight



Eco Power Timer



Model No.	S 43	S 49	S 55
Display Size (inch)	43" (108cm)	49" (124cm)	55" (139cm)
Resolution	1080 x 1920 HD		
Display Area (mm)	394.8 x 700.5 mm	603 x 1073.5 mm	680.4 x 1209.6 mm
Aspect Ratio	9 : 16		
Brightness (cd/m ²),	350		
Colour	16.7M		
Viewing Angle	178°x 178°		
Contrast Ratio	1000:1	1000:1	4000:1
Media Formats	Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG)		
Media Resolution	2160 x 3840 Pixels		
Expendable Memory	up to 32GB		
Processor (Optional)	Rockchip® 3368 (1.8GHz, octa core)		
RAM (Optional)	2 GB		
Flash (Optional)	16 GB EMMC		
USB & HDMI	2 USB & 1 HDMI		
LAN (Optional)	10M/100M Ethernet 1		
Wi-Fi (Optional)	802.11b/g/n Ethernet (Network version screen only)		
OS (Optional)	Android 5.1.1		
Speaker	10W (2Nos.)		
Input	100V~240V AC (50/60 Hz)		
Operating Temperature	0° C - 45° C		
Storage Temperature	-30°C ~ 55° C		
Operating Humidity	10% ~ 80% RH		
Storage Humidity	5% ~ 95% RH		
Included	Remote control, Power cable		

Pyrotech Electronics Pvt. Ltd. Unit#2
E-329, Road No 12, M.I.A., Madri, Udaipur - 313003